



Ultra Short Throw Interactive Projector

FEATURES

- Ultra short throw lens to make 100 inch screen at only 44cm away
- 3,500 ANSI lumens of brightness, WXGA resolution, and 10,000:1 contrast ratio for clear, crisp and bright projection
- Built-in interactivity for multi users with 2 pens or optional finger touch
- 2x 10W speakers and microphone input ensure you are clearly heard
- Long lasting life with up to 12,000 hours lamp-life
- Eco Friendly and Energy Saving with sleep timer and also auto-power-off when there is no signal input
- Integrated network monitoring and management solutions including Crestron® RoomView™, and etc.
- 5 year education warranty
- Compatible with NovoConnect wireless collaboration solution



Ultra short throw lens can make 100 inch projection screen from as little as 44cm away

The DW771USTi is the ultimate interactive ultra-short-throw projector for the education with 3500 lumen of brightness and WXGA resolution . The projector offers a 100 inch diagonal 2.15 metre wide projection image from as little as 44cm away from the screen surface. As well as delivering an optimal viewing experience, the DW771USTi ensures a high sound quality thanks to in-built 2x10W speakers. The DW771USTi supports multi-users with dual pen functionality and an optional Finger Touch Unit with 10 points. It is HID driver-free and, for further convenience, the interactive pen can be used like a computer mouse without the complications of installing a driver. This projectors it a robust alternative to flat panels when a 100 inch size screen is required.



DW771USTi SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3500 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	UHD (3840 x 2160) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/- 40°
Optical	Throw Ratio	0.35:1
	Zoom Ratio	Fixed 1x
	Lens Shift (Based on Full Image Height)	Limited Lens Shift Vertical ±1.7%
	Image Size (Diagonal)	80"- 100"
	Projection Distance	283 - 446 mm
	Projection Lens	F = 2.5, f = 5.1 mm
	Offset (Based on Full Image Height)	120%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x1), HDMI v 2.0 (x2), Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, 3D-Sync, USB A (Power Only), USB miniB (Interactivity), USB B (Service), Microphone (Mini-Jack)
General	Dimensions (W x D x H)	287.7 x 374.5 x 122.6 mm (not including height of mirror)
	Lamp Life and Type	6,000 / 12,000 Hours (Normal / Eco. Mode)
	Speakers	10W x 2
	Noise Level	33dB / 29dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), IR interactive Pen / nbr, AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811123650'SVV), 3D Glasses P/N (3534257700), Universal Wall Mount (T/R 0.35) (%WM-3), Remote Control P/N (5041841300)
	Warranty	Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	UPC Code	813097024275